This Page Is Inserted by IFW Operations and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.

THIS PAGE BLANK USPRO

SPECIFICAT

588,386



Application Date: Feb. 14, 1945.

Complete Specification Left: Nov. 28, 1945.

Complete Specification Accepted: May 21, 1947.

PROVISIONAL SPECIFICATION

Improvements in Containers

We, Paton, Calvert and Company LIMITED, a British Company, of 201, Binns Road, Old Swan, Liverpool, 13, in the County of Lancaster, and WALTER PATON, a British Subject, of the said Company's address, do hereby declare the nature of this invention to be as follows:-

This invention relates to improvements 10 in containers, especially for containing fine powder such as talcum. In these containers it is usual to provide a large fillingorifice, a perforated sprinkler and an imperforate cap. The object of the present. 15 invention is to provide a simplified con-

struction. The invention consists in a container having a metal top with an annular neck smaller than the top, a perforated top to 20 fit over said neck with means to snap it in position, and an imperforate cap to fit removably over said perforated top. Preferably the annular neck is provided with an external groove to receive a perforated disc 25 having a springy depending flange to snap

into the said groove.

The invention is described by way of example in the accompanying drawings, in which:-

Fig. 1 is a vertical section with inner 30 and outer caps in position, while

Figs. 2—4 are perspective views of the components ready for assembly.

In these drawings a cylindrical cardboard (or metal) body 1 is provided with 86 a metal top 2 having an annular neck 3 which is inwardly turned over. 4 is the central hole for filling and 5 is a groove as shown more clearly in Fig. 4. Fig. 3 shows a snap-on lid 6 having perforations, 40 while 7 is a friction cap.

The body is closed at the bottom by a metal disc. The container is filled through the large orifice 4, the sprinkler top 6 is then snapped on to the flange 3 and the 45 cap 7 is removably placed in position.

Dated this 12th day of February, 1945. W. P. THOMPSON & CO.,

12, Church Street, Liverpool, 1, Chartered Patent Agents.

COMPLETE SPECIFICATION

Improvements in Containers

We, PATON, CALVERY AND COMPANY rim so that it may be snapped over a flange LIMITED, a British Company, of 201, Binns Road, Old Swan, Liverpool, 13, in 50 the County of Lancaster, and WALTER PATON, a British Subject, of the said Company's address, do hereby declare the nature of this invention and in what manner the same is to be performed, to be 55 particularly described and ascertained in

and by the following statement:—
This invention relates to improvements in containers, especially for containing

fine powder such as talcum.

In these containers it is usual to provide a large filling orifice, a perforated sprinkler and an imperforate cap. The object of the present invention is to provide a simplified construction.

Cap closures for containers are known in which a cap has either a plurailty of dependent fingers or a lower axially slitted groove as shown more clearly in Fig. 4.

on a container mouth.

According to the present invention a container having an opening at one end is closed by a perforate cap having an uninterrupted rim which can snap over a flange around the said opening.

The invention is further described with 76 reference to the drawings accompanying the provisional patent application, in which:-

Fig. 1 is a vertical section with inner 80 and outer caps in position, while Figs. 2-4 are perspective views of the

components ready for assembly.

In these drawings a cylindrical cardboard (or metal) body 1 is provided with a metal top 2 having an annular neck 3 85 the edge of which is inwardly turned over. 4 is the central hole for filling and 5 is a

[Price 1/-]

Fig. 3 shows a snap-on lid 6 having perforations, while 7 is a detachable closure

The body is closed at the bottom by a metal disc. The container is filled through the large orifice 4. The sprinkler cap 6 is then snapped on to the neck 3.

The uninterrupted inturned edge of the perforate cap 6 is of slightly smaller. 10 diameter than the external diameter of the flange 8 around the filling opening 4 and engages in the groove of the neck 5. The cap 7 is removably placed in position and fits frictionally to the neck of said con-15 tainer below said perforate cap where this neck, as shown in Figure 4, is of greater

Having now particularly described and diameter than the flange 8. ascertained the nature of our said inven-20 tion and in what manner the same is to be

performed, we declare that what we claim 18 A container having an opening at

an uninterrupted rim which can snap over 25 a flange around the said opening.

2. A container, the body of which has neck provided with a filling opening. a groove being disposed below the rim of the neck for the acceptance of the lower 30 uninterrupted rim of a perforated cap, which rim is of slightly smaller internal diameter than the external diameter of the rim of the neck to snap into the groove

3. A container as claimed in claim 1, below it. in which a detachable closure cap fits frictionally to the neck of said container below said perforated cap to enclose the

4. A container constructed as particularly described with reference to the drawings accompanying the provisional

specification. 27th day of November, 1945.

Dated this 27th day of November, 1945.

W. P. THOMPSON & CO.,
W. P. THOMPSON & CO., 12, Church Street, Liverpool, 1, Chartered Patent Agents.

one end closed by a perforate cap having Leamington Spa: Printed for His Majesty's Stationery Office, by the Courier Press. 1947. Leamington ups: Frinted for rue majesty 8 prestionery omes, by the Course Published at The Patent Office, 25, Southampton Buildings, London, W.C.2, from which Published at The Patent Office, 25, Southampton Buildings, London, W.C.2, from which copies, price ls. Od. each (inland) ls. 1d. (abroad) may be obtained.

H.M.S.O.(Ty.P.) .

·: .'

** FAGE BLANK (USPTO) والإيراني والمرازي 77. (T. 14.

40000

1. 2 - 2

and the second of the comparison of the property of the property of the property of

energy of an engineering and an engineering groves we estange about the other of ... v e turn am fazi bas nest at a f in the first of the trade of the first and higher emigration especies. e transport of objections of the

e or usale months of efficient of a control of the AND THOSE IT IS TO BE TO BE THE STORE OF THE SECTION OF For the vigital control and single collection and displayed and displaye SECURE EST PORTUGISMOS

The state of the second second